



2012 People GT 200i

From the newly designed People series emerges the **People GT 200i**, now with a powerful 205cc liquid cooled engine, new dual cradle frame and electronic fuel injection. The five position adjustable rear suspension, 16" aluminium wheels and fold away foot pegs provide the comfort and stability expected of the People series scooters. You'll only need to ride it once to appreciate the performance, style and balance of the all new People GT from KYMCO. It's distinctive contemporary design, impressive ergonomic comfort, highway capability, additional storage space and modern technology gives this scooter instant rider appeal.



Additional Features: 16 inch / 5 spoke aluminum rims, electronic fuel injection, liquid cooling, five position adjustable rear shock, colour matched rear top case, low center of gravity, indigo lighting on analogue instrument cluster with LCD clock and service indicator, stylish bodywork, sleek colours, factory windscreen, DOT approved headlight with high and low beam, LED indicator lighting, spring loaded side stand, sturdy center stand, folding passenger foot pegs, under seat storage with 12V outlet, front glove box, rear top case & centre hook.

Available Accessories:

Scooter Cover

Wireless Brake Light

*Please contact your local authorized KYMCO dealer for a range of other aftermarket accessories.

All KYMCO Scooters come with a 2 year limited warranty!

Engine type	Liquid cooled, Single cylinder, 4 stroke
Displacement	205 cc
Bore & stroke	66 x 60 mm
Compression ratio	10.3-1
Valve train	S.O.H.C., chain drive, 4 valve
Fuel delivery	Electronic Fuel Injection
Transmission	Automatic CVT
Front suspension	Telescopic forks
Rear suspension	Adjustable Shocks
Tires	100/70-16 Front; 140/70-16 Rear
Brakes Front	Drilled Disk / 3 Piston Caliper
Rear	Disk / Dual Piston Caliper
Seat height	810 mm
Wheel base	1450 mm
Fuel capacity	9 litres
Dry weight	165
Available Colors:	





2012 People GT 200i

Engine Type	Liquid cooled, Single cylinder, 4 stroke, 4 valve
Displacement	205 cc
Bore & stroke	66 x 60 mm
Compression ratio	10.3:1
Valve train	S.O.H.C., chain drive, 4 valve
Fuel Delivery	Electronic Fuel Injection
Ignition	Electronic Fuel Injection
Transmission	Automatic CVT
Spark plug	NGK C7HSA
Emission	CEPA Environmental Registered
Fuel capacity	9 litres
Tires	110/70-16 front; 140/70-16 rear
Front Suspension	Telescopic Forks
Rear Suspension	Five Position Dual Adjustable Shocks
Front Brakes	Drilled Disk / 3 Piston Caliper
Rear Brakes	Drilled Disk / Dual Piston Caliper
Instrument cluster	Analog Speedometer and Fuel Gauge, with LCD Trip Meter, Service Indicator, and Clock
Stands	Centre and Side Stands
Storage compartment	Rear Top Case, Under Seat & Front Glove Box
Complete Size (L x W x H)	2130 x 750 x 1450 mm
Seat Height	810 mm
Dry weight	165kg
Riders	2 Riders with foldable foot pegs
Warranty	Two year limited warranty

