



4x4



2012 MXU 500i IRS

The **MXU 500i IRS** is a multi-functional utility ATV with features for sport, leisure, and work. It is equipped with a liquid-cooled KYMCO engine which provides an unfailing supply of power with high torque in low rpm. A 1/2 ton standard towing capacity, welded-in front winch plate, electronic locking front differential, standard aluminium mag wheels, and disk brakes in both front and rear with stainless steel braided brake lines equip the MXU 500 to tackle any situation.




Additional Features: Manual choke, fuel injection, electronic locking front differential, 2WD / 4WD shift on the fly, aggressive tires and aluminium mag wheels, braided stainless steel brake lines, cross drilled rotors, two single piston front and rear calipers, dual A-arm front and rear suspension, digital instrumentation, large fender flairs, bright halogen headlamps, winch mount plate built-in, sturdy front and rear racks, large front grille, 2 inch receiver.

Available Accessories:

- EPI Clutch kit
- Heavy Duty Brake Pads
- Wireless Brake Light
- 12v accessory outlet
- Warn Winch RT25

All KYMCO ATVs come with a 1 year limited warranty!

Engine type	Liquid cooled, Single cylinder, 4 stroke
Displacement	498.5cc
Bore & stroke	92x75mm
Compression ratio	10.5: 1
Valve train	D.O.H.C., chain drive
Fuel delivery	Electronic Fuel Injection
Transmission	Automatic CVT with High, Low, Neutral, Reverse and Park
Front suspension	Dual A-Arm
Rear suspension	Dual A-Arm
Tires	25/8-12 front 25/10-12 rear
Brakes Front	Dual Drilled Disks / Dual Single Piston Calipers
Rear	Single Drilled Disk/ Dual Single Piston calipers
Seat height	857 mm
Wheel base	1293 mm
Fuel capacity	17 litres
Dry weight	312 kg
Towing Capacity	453 kg
Available Colors:	





2012 MXU 500i IRS

Engine Type	Liquid cooled, Single cylinder, 4 stroke
Displacement	498.5 cc
Bore & stroke	92x75mm
Compression ratio	10.5: 1
Valve train	D.O.H.C., Chain Drive
Fuel Delivery	Electronic Fuel Injection
Ignition	Electronic Fuel Injection
Transmission	Automatic CVT
Transfer Gearshift Pattern	L/H/N/R/P
Spark plug	CR7E
Emission	CEPA Environmental Registered
Fuel tank capacity	17 litres
Tires	25/8-12 Front; 25/10-12 Rear
Front Suspension	Dual A-Arm
Rear Suspension	Dual A-Arm
Front Brakes	Dual Drilled Disks / Dual single piston calipers
Rear Brakes	Single Drilled Disk / Dual single piston calipers
Type Speedometer	Digital with Speedometer, Fuel Level and Gear indicator
Complete Size (L x W x H)	2203 x 1223 x 1240 mm
Seat Height	857 mm
Dry weight	312 kg
Ground Clearance	10.25 inches
Towing Capacity	453 kg
Maximum passengers	1
Warranty	One year limited warranty



Warning: KYMCO vehicles meet all applicable Canadian Motor Vehicle Safety and CEPA standards. Always wear a helmet, eye protection and protective clothing. Avoid excessive speed. Never engage in stunt riding. Never ride under the influence of alcohol or drugs. Take an approved rider training course.